



Introduction

The Atлона **AT-OME-CS31-SA** is an AV presentation and collaboration system for classrooms and conference rooms. It features a 3x1 HDMI® switcher, 50 watt mixer amplifier, and USB 3.0 hub.

The HDMI switcher is HDCP 2.2 compliant and supports up to 4K/60 4:4:4 plus HDR formats for common inputs such as laptops, computers, and document cameras routed to the output connected to a projector or display. The OME-CS31-SA amplifier delivers either two channels of 25 watts or a single channel of 50 watts into 4 or 8 ohms. It features one balanced stereo audio input and two unbalanced stereo audio inputs with independent level control for each. A balanced stereo line level output allows the mixed signal to be passed to an assistive listening system or separate amplifier. The OME-CS31-SA includes USB 3.0 interfaces for two host computers, plus four peripheral devices such as a camera, speakerphone, interactive display, keyboard, mouse, or storage device.

The OME-CS31-SA includes unique capabilities intended for education applications. Ducking automatically lowers the level on all other program audio sources when the teacher speaks into their microphone connected to the balanced line input. PA sense mutes the output of the amplifier whenever it detects activity on the school public address system. Both features ensure important lesson material and announcements are heard clearly.

For control, the OME-CS31-SA includes dual Ethernet ports and two RS-232 ports for automated operation of the switcher itself and other system components from Velocity™ or a third-party control system. The low profile enclosure allows the OME-CS31-SA to be mounted in a variety of locations such as behind a display or under a desk or table.

Applications

- Classrooms**
 In addition to the AV switching, audio amplification, USB routing, and control needed by modern classrooms, the OME-CS31-SA provides additional features for education environments including ducking program audio for an instructor microphone and muting the system for public address messages.
- Conference Rooms**
 The OME-CS31-SA is an all-in-one solution for hybrid meeting spaces that need AV switching, audio amplification, USB routing, and display control.

Key Features

- 3x1 HDMI® switcher for common source devices such laptops, computers, and document cameras as well as output to a projector or display.
- Integrated USB hub with two 3.0 type B host ports and four 3.0 type A peripheral ports.
- 2 x 25 watts @ 4/8 ohms amplifier (stereo or dual mono) or 1 x 50 watts @ 4/8 ohms (bridged).
- One balanced stereo line level input and two unbalanced stereo line level inputs on 3.5 mm connections.
- Balanced stereo line level output allows the mixed signal to be passed to an assistive listening system or separate amplifier.
- Powerful on-board digital signal processing
 - » Mix 3 line inputs, de-embedded HDMI audio, and USB audio to the amplifier and line outputs.
 - » Mix 3 line inputs and de-embedded HDMI audio to the USB audio output.
 - » Acoustic Echo Cancellation (AEC) automatically eliminates echo for remote USB audio.
- Supports mixing 3 line inputs, de-embedded HDMI, and USB audio to the amplifier and line outputs.
- Ducking lowers the level of all inputs when audio, such as a teacher microphone, is present on the balanced audio input.
- Supports audio mute with contact closure or PA sense so announcements can be heard clearly.
- Dual Ethernet ports and integrated network switch allows a single connection to an AV LAN for IP control of a display and the switcher.
- Two RS-232 ports for control of the switcher or peripheral devices.
- Two digital I/O ports for automated control from occupancy sensors or other third party devices.
- 5V USB charging port for powering external devices such as a Bluetooth® receiver.
- Energy Star® qualified for power efficiency and cost savings.
- Automatic display control changes display power state via CEC, IP, or RS-232 based on active or standby mode of the switcher or status of an AT-OCS-900N network-enabled occupancy sensor or other sensors connected to the digital I/O ports.
- Auto-switching selects active input when sources are connected or if there is a change in source power status.
- Manages EDID communications with the source through the connected display's EDID or internally stored EDID.
- HDCP 2.2 compliant.
- 4K/UHD capability @ 60 Hz with 4:4:4 chroma sampling.
- Supports HDR10, HLG, and Dolby® Vision™ HDR formats.
- Intuitive GUI-based configuration using integrated web server.
- Front panel LED indicators provide status for power, input selection, and LAN.
- Low profile enclosure for mounting behind a display or under a desk or table.

Specifications

| Video | | |
|--------------------|---|--|
| Signal | Input - HDMI Output - HDMI | |
| Copy Protection | HDCP 2.2 | |
| Pixel Clock | 600 MHz | |
| UHD/HD/SD | 4096x2160 (DCI) @ 24/25/30/50/60 Hz 3840x2160 (UHD) @ 24/25/30/50/60 Hz 1920x1080p @ 23.97/24/25/29.97/30/50/60 Hz 1920x1080i @ 50/60 Hz 1280x720p @ 30/50/60 Hz | 720x576p @ 50 Hz 720x576i @ 25/50 Hz 720x480p @ 60 Hz 640x480p @ 60 Hz 640x480i @ 60 Hz |
| VESA | 2560x2048 2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1600x900 1440x900 1400x1050 | 1366x768 1360x768 1280x1024 1280x800 1280x768 1152x768 1024x768 800x600 640x480 |
| VESA 21:9 | 5120x2160 @ 30 Hz 4:4:4 3840x1600 @ 60 Hz 4:4:4 3840x1600 @ 30 Hz 4:4:4 3440x1440 @ 60 Hz 4:4:4 | 3440x1440 @ 50 Hz 4:4:4 3440x1440 @ 30 Hz 4:4:4 2560x1080 @ 60 Hz 4:4:4 2560x1080 @ 30 Hz 4:4:4 |
| Color Space | YUV, RGB | |
| Chroma Subsampling | 4:4:4, 4:2:2, 4:2:0 | |
| Color Depth | 8-bit, 10-bit, 12-bit | |
| HDR | HDR10, Hybrid-Log Gamma (HLG), and Dolby® Vision™ @ 60 Hz | |

| Audio | | | |
|---------------------------|--|---|--|
| HDMI Pass-Through Formats | LPCM 2.0 LPCM 5.1 LPCM 7.1 | Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos® | DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X® |
| Bit Depth | Up to 24 bits | | |
| Sample Rate | 32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz | | |
| Analog Audio | | | |
| Format | Stereo 2-Channel | | |
| Balanced Input | +4 dBu | | |
| Unbalanced Input | -10 dBV | | |
| Amplifier Output | 2 x 25 W @ 4 or 8 Ω Frequency Response: 20 Hz to 20 kHz +/- 2 dB THD+N: < 0.1% @ 1 kHz SNR: 85 dB | | |
| Balanced Output | +4 dBu Frequency Response: 20 Hz to 20 kHz +/- 0.5 dB THD+N: < 0.025% from 20 Hz to 20 kHz | | |

| USB | |
|-------------------|------------|
| Compliance | 3.0 |
| Maximum Data Rate | 5 Gbps |
| Internal Hubs | 2 USB hubs |

| Ethernet | |
|-------------------------|--|
| Port | 2 x RJ45 |
| Standards and Protocols | HTTP, HTTPS, Telnet, SSH, JSON over WebSockets |
| Speeds | 10/100/1000 Mbps |
| Addressing | DHCP, Static – selectable through built-in web server and API commands |

| RS-232 | |
|------------|--|
| Port | 2 x 3-pin captive screw |
| Use | Unit and external device control and configuration |
| Baud Rates | 9600, 19200, 38400, 57600, 115200 |
| Data Flow | Bidirectional |

| CEC | |
|------------|-------------------------------------|
| Ports | 1 x HDMI OUT, Type A, 19-pin female |
| Triggering | Through HDMI |

| Resolution / Distance | 4K/UHD - Feet / Meters | | 1080p - Feet / Meters | |
|-----------------------|------------------------|---|-----------------------|----|
| HDMI IN/OUT | 15 | 5 | 30 | 10 |

| Buttons and Indicators | |
|---|--|
| Buttons: INPUT | 1 x momentary, tact-type |
| Indicators: PWR LAN, IN1, IN2, IN3 | 1 x LED, multicolor, green/red 4 x LED, green |

| Connectors | |
|------------------------------|---------------------------|
| HDMI IN | 3 x Type A, 19-pin female |
| HDMI OUT | 1 x Type A, 19-pin female |
| HOST | 2 x USB type B, female |
| MIC | 1 x RJ45 |
| VOICE L/R | 1 x 5-pin captive screw |
| L/R | 2 x 3.5 mm mini-stereo |
| 5V | 1 x USB type A, female |
| FW | 1 x USB type C, female |
| LAN | 2 x RJ45 |
| TRIGGER I/O | 2 x 4-pin captive screw |
| RS-232 | 2 x 3-pin captive screw |
| PA SENSE TRIGGER | 1 x 2-pin captive screw |
| PA SENSE GND/25V/75V/100V | 1 x 4-pin captive screw |
| AMP OUT | 1 x 4-pin captive screw |
| AUDIO OUT | 1 x 5-pin captive screw |
| HUB | 4 x USB type A, female |
| 24V / 5A | 1 x 4-pin DIN |

| Environmental | Fahrenheit | Celsius |
|-------------------------|----------------------------|------------|
| Operating Temperature | +32 to +122 | 0 to +50 |
| Storage Temperature | -4 to +140 | -20 to +60 |
| Operating Humidity (RH) | 20% to 90%, non-condensing | |

| Power | |
|-----------------------|---|
| Consumption (max.) | 87.4 W |
| BTU/h | 298.2 |
| External Power Supply | 100 - 240 V AC, 50/60 Hz Output: 24 V / 5 A DC |

| Dimensions (H x W x D) | Inches | Millimeters |
|------------------------|---------------------|-----------------|
| Unit | 0.98 x 11.81 x 8.27 | 25 x 300 x 210 |
| Power Supply | 1.6 x 2.6 x 6.2 | 40.6 x 66 x 157 |

| Weight | Pounds | Kilograms |
|--------|--------|-----------|
| Device | 3.8 | 1.7 |

| Certification | |
|---------------|--|
| Device | CE, RoHS, FCC |
| Power Supply | CE, FCC, UL, CUL, TUV-GS, CB, PSE, CCC |

| Compliance | |
|------------|-----|
| NDA-889 | Yes |

| Warranty | |
|----------|--|
| 3 years | View the full warranty information here: https://atlona.com/warranty |

Copyright, Trademark, and Registration

© 2024 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).